

JIT Components, Inc.


10930 Endeavour Way, Unit A Seminole FL 33777

Phone: (727) 544-9050

Fax: (727) 544-9273

Email: service@jit-components.com

PM4848E



FRONT

Single display version (1D): no. 3 DIGIT (0.4" h = 7 mm) no. 4 SWITCHES max. (h = 7 mm) no. 6 LED max. (dia. 3 mm)

Double display version with main indicator (2D): n. 4 DIGIT (0.3"; h = 7 mm) Secondary indicator: n.4 DIGIT (0.2"; h = 6 mm) n. 4 SWITCHES max. (h = 7 mm) n. 6 LED max. (dia. 3 mm)

Special version with space for 29 x 40 indicator (S1): n. 4 SWITCHES max. (h = 7 mm) available upon request only.

REAR

Version with 18 screw type connections.

Version with 10 screw type connections.

Material

Self-extinguishing ABS

PM4848E

Available Complete Cases

DIMENSIONS

MM

IN

W

H

L

W

H

L

02.108 L069

48

48

69

1.89

1.89

2.72

02.108 L083

48

48

83

1.89

1.89

3.27

02.108 L109

48

48

109

1.89

1.89

4.29

OPTIONS

P02540001D

Frame EV1D

P02540002D

Frame EV2D

P02540001S

Frame EVS1

P02330201C

48x48E rear frame for terminal type MVI

21.190 2062

Terminal, direct insertion pitch 6,35, black, type MVI2, 2 poles

21.190 3062

Terminal, direct insertion pitch 6,35, black, type MVI3, 3 poles

21.190 1122

Terminal, direct insertion pitch 12,7, black, type MVIB, 2 poles

21.190 2122

Terminal, direct insertion, black, type MVIAO

21.190 2002

Terminal, direct insertion, black, type MVIBO

21.190 3002

CODU one single pole connector

P0254000CU

Socket 10 poles MST 410

P02540010Z

Socket 10 poles MST 410

Machining and printing