

JIT Components, Inc.


10930 Endeavour Way, Unit A Seminole FL 33777

Phone: (727) 544-9050

Fax: (727) 544-9273

Email: service@jit-components.com

PM4896B / PM4896M



This enclosure can easily be assembled without the use of fixing screws. The PCB is inserted from the rear side of the enclosure using the internal PCB guides and it is fixed by the rear frame with a snap-lock mechanism. Either the front or the rear panels can be inserted into the enclosure by a snap-lock mechanism. Lengths (L) different from the standard ones are available upon request.

Material		Self-extinguishing PPO				
PM4896M	Available Complete Cases					
DIMENSIONS	MM			IN		
	W	H	L	W	H	L
01.113 L057	48	96	57	1.89	3.78	2.25
01.113 L075	48	96	75	1.89	3.78	2.95
01.113 L100	48	96	100	1.89	3.78	3.94
01.113 L124	48	96	124	1.89	3.78	4.88
PM4896B	Available Complete Cases					
DIMENSIONS	MM			IN		
	W	H	L	W	H	L
01.109 L057	48	96	57	1.89	3.78	2.25
01.109 L075	48	96	75	1.89	3.78	2.95
01.109 L100	48	96	100	1.89	3.78	3.94
01.109 L124	48	96	124	1.89	3.78	4.88
OPTIONS						
06.293 0000	Front panel, anodized, aluminium, mat)					
06.253 0000	Front panel, PPO UL94 V-0, black					
06.352 0000	Front panel, Plexiglass, transparent					
06.202 0000	Front panel, Plexiglass red, transparent					
06.342 0000	Front panel, PC permeable to infra - red light					
06.312 0000	Rear panel, anodized Aluminium, mat					
06.273 0000	Rear panel, PPO UL 94 V-0, black					
06.372 0000	Rear panel, PVC UL 94 V-0, black					
06.364 0000	8 PIN rear panel with mounted pins (OCTAL)					
06.368 0000	11 PIN rear panel with mounted pins (UNDECAL)					
03.432 0000	Protection Cover IP54					
03.442 0000	Protection Cover IP65					
	Machining and printing					