

POLYCARBONATE (LIGHT GRAY AND CLEAR)

UL94V-2 FLAMMABILITY RATING

<UL FILE #E41613>

UV STABILIZED

SERVICE TEMPERATURE RANGE:

-40°C TD +120°C

ABS (DARK GRAY)

UL94-HB FLAMMABILITY RATING

<UL FILE #E56070>

SERVICE TEMPERA



NOTE: ALL DIMENSIONS HAVE ± 0.015 TOLERANCE UNLESS OTHERWISE SPECIFIED.



JIT
Components, Inc.

SE1335, SE1335C, SE1335DG
ENCLOSURE LAYOUT

www.jit-components.com

REV	DATE	DESCRIPTION	BY			www.jit-components.com	
				SEI1335, SEI1335C, SEI1335DGE ENCLOSURE LAYOUT			
				JIT Components, Inc.			
				TOLERANCES UNLESS OTHERWISE SPECIFIED 2 PLACE DECIMALS (IN) ± .02 3 PLACE DECIMALS (IN) ± .005 4 PLACE DECIMALS (IN) ± .0005 ANGLES ± .5° METRIC (MM) ± .15		DESIGNER	DATE 03/28/00
						SHEET	SCALE
							REV
				MATERIAL			