

PART NAME	LARGE NON-METALLIC ENCLOSURE (STYLE E)									
	SEE10553 AND SEE10573									

MATERIAL:

SOLID BODY & COVER

ABS/PC BLENDED PLASTIC

UL94-5VB FLAMMABILITY RATING

-40°C TO +70°C TEMPERATURE RANGE

POLYCARBONATE PLASTIC

UL94-V0 FLAMMABILITY RATING

-40°C TO +70°C TEMPERATURE RANGE

UV STABILIZED

FINISH:

BODY

LIGHT GRAY

COVER

LIGHT GRAY OR CLEAR

PANEL

ANODIZED

COVER IS GASKETED.

UNIT COMES COMPLETE WITH

FLOOR (4) STAINLESS STEEL

WALL MOUNTING BRACKETS.

(NOT SHOWN)

INDUSTRY STANDARDS:

UL508 TYPE 1, 2, 4, 4X INDOOR, 12 & 13

NEMA TYPE 1, 2, 4, 4X, 12 & 13

IEC529, IP66

AIR AND MOISTURE VENTS, GALVANIZED

STEEL INTERNAL PANEL AND STAINLESS

STEEL LOCKING HASP ARE NOT INCLUDED,

BUT CAN BE PURCHASED SEPARATELY.

PANEL

0.078 THICK ALUMINUM

LATCHES & HINGES

NON-METALLIC

WALL MOUNTING BRACKETS

STAINLESS STEEL

VIEW LESS COVER

0.570 [14] DIA. BOSS WITH M5 x 0.8mm THREADED BRASS INSERT (4) PLACES FAR SIDE

VIEW LESS COVER AND SWINGFRAME PANEL

0.984 [25] TYP.

0.570 [14] DIA. BOSS WITH M5 x 0.8mm THREADED BRASS INSERT (4) PLACES

0.472 [12] DIA. BOSS WITH 0.166 [4] DIA. HOLE x 0.340 [9] DEEP (52) PLACES

VIEW LESS COVER

0.078 [2]

0.126 [3]

0.276 [7] (INSIDE)

0.380 [10] (INSIDE)

INDUSTRY STANDARDS:

UL508 TYPE 1, 2, 4, 4X INDOOR, 12 & 13

NEMA TYPE 1, 2, 4, 4X, 12 & 13

IEC529, IP66

AIR AND MOISTURE VENTS, GALVANIZED

STEEL INTERNAL PANEL AND STAINLESS

STEEL LOCKING HASP ARE NOT INCLUDED,

BUT CAN BE PURCHASED SEPARATELY.

PART NO.		DIMENSIONS																					
SOLID COVER	CLEAR COVER	A	B	C	D	E	F	G	H	J	K	L	M	N	P	R	S	T	U	V	W	X	Y
SEE10553	SEE10573	14.640 [372]	13.750 [349]	12.768 [324]	12.158 [309]	11.643 [296]	10.824 [275]	19.170 [487]	18.330 [466]	17.392 [442]	16.690 [424]	16.138 [410]	14.760 [375]	6.666 [169]	1.185 [30]	18.500 [470]	18.335 [466]	13.980 [355]	13.810 [337]	13.271 [470]	12.516 [318]	18.110 [460]	17.088 [434]

NOTE: ALL DIMENSIONS HAVE ±0.039 [±1] TOLERANCE UNLESS OTHERWISE SPECIFIED

DIMENSIONS = INCHES [MILLIMETERS]