




JIT Components, Inc

DR1050

	COMPONENT	DIMENSIONS					
		MM			IN		
		W	L	H	W	L	H
	DR1050	86	105	58	3.39	4.13	2.28
	BASE PCB	82	99	1.6	3.23	3.90	.062

SPECIFICATIONS

Maximum Terminals	36	Maximum Load	10 amp
Maximum Temperature	100° C	Flammability	UL94 V0

PART DATA

DESCRIPTION	MATERIAL	UL INFO		COLOR	PART NO.
		FILE	FLAM		
DR1050 Base w/Clip & 2 Screws	Noryl VO1550	E45329	V0	Black	4969021051
DR1050 Din Rail Clip	Delrin N9000			Black	0669000604
DR1050 Housing, Fixed	Lexan 940	E45329	V0	Gray	4969001052
DR1050 Housing, Fixed, Vented	Lexan 940	E45329	V0	Gray	4969001057
DR1050 Housing, Fixed, 1-18 Open Only	Lexan 940	E45329	V0	Gray	4969011059
DR1050 Housing, Pluggable	Lexan 940	E45329	V0	Gray	4969001051
DR1050 Housing, Pluggable, Vented	Lexan 940	E45329	V0	Gray	4969001058
DR1050 Housing, Closed	Lexan 940	E45329	V0	Gray	4969001050
DR1050 Housing, Closed, Vented	Lexan 940	E45329	V0	Gray	4969001059
DR1050 Housing, Knockouts	Lexan 940	E45329	V0	Gray	4969001055
DR1050 Housing, Knockouts, Vented	Lexan 940	E45329	V0	Gray	4969001056
DR1050 Transparent Lid	Lexan 940	E45329	V0	Clear	4969011050
Terminal Block, Fixed, 18, 5.00	Polycarbonate	E150931	V0	Gray	3950141808
Terminal Block, Pluggable, Plug, 18, 5.00	Polyamide	E48521	V0	Black	39870-0118
Terminal Block, Pluggable, Hdr, 18, 5.00	Nylon 6.6	E48521	V0	Black	39870-0718
Light Conductor	PVC			Clear	4972011259
Spindle				Gray	0209013501
Screw, Self-Cutting, 1 Piece	Steel				7006102965
Surface Mount Tabs	Noryl VO1550	E45329	V0	Black	0669000610
Machining and Printing_					