




JIT Components, Inc

DR350

	COMPONENT	DIMENSIONS					
		MM			IN		
		W	L	H	W	L	H
	DR350	86	35	58	3.39	1.38	2.28
BASE PCB	82	29.2	1.6	3.23	1.15	.062	

SPECIFICATIONS

Maximum Terminals	10	Maximum Load	10 amp
Maximum Temperature	100° C	Flammability	UL94 V0

PART DATA

DESCRIPTION	MATERIAL	UL INFO		COLOR	PART NO.
		FILE	FLAM		
DR350 Base w/Clip & 2 Screws	Noryl VO1550	E45329	V0	Black	4969002351
DR350 Din Rail Clip	Delrin N9000			Black	0669000605
DR350 Housing, Fixed	Lexan 940	E45329	V0	Gray	4969000352
DR350 Housing, Fixed, Vented	Lexan 940	E45329	V0	Gray	4969000354
DR350 Housing, Fixed, 1-5 Open Only	Lexan 940	E45329	V0	Gray	4969000359
DR350 Housing, Pluggable	Lexan 940	E45329	V0	Gray	4969000351
DR350 Housing, Pluggable, Vented	Lexan 940	E45329	V0	Gray	4969000355
DR350 Housing, Closed	Lexan 940	E45329	V0	Gray	4969000350
DR350 Housing, Closed, Vented	Lexan 940	E45329	V0	Gray	4969000356
DR350 Housing, Knockouts	Lexan 940	E45329	V0	Gray	4969000353
DR350 Housing, Knockouts, Vented	Lexan 940	E45329	V0	Gray	4969000357
DR350 Transparent Lid	Lexan 940	E45329	V0	Clear	4969001350
DR350 Gray Lid	Lexan 940	E45329	V0	Gray	4969001351
Terminal Block, Fixed, 5, 5.00	Polycarbonate	E150931	V0	Gray	3950145108
Terminal Block, Pluggable, Plug, 5, 5.00	Polyamide	E48521	V0	Black	39870-0105
Terminal Block, Pluggable, Hdr, 5, 5.00	Nylon 6.6	E48521	V0	Black	39870-0705
Light Conductor	PVC			Clear	4972011259
Spindle				Gray	0209013501
Screw, Self-Cutting, 1 Piece	Steel				7006102965
Surface Mount Tabs	Noryl VO1550	E45329	V0	Black	0669000610
Machining and Printing					