

# JIT Components, Inc

## PLUGS

**ST-1 STH-1**



**ST-2**



**ST-1-90D**




## SOCKETS

**GT-3**



**GTO-5**




**GT-10**



**GT-15**



**GT-30**



## GENERAL SPECIFICATIONS

Parameter	ST-1 ST-2	STH-1	GT-3	GTO-5 GTOL-5	GT-10	GT-15	GT-30
<b>Current Rating</b>	10A	15A	3A	5A	10A	15A	30A
<b>Contact Resistance</b>	5 Mohms Max	5 Mohms Max	10 Mohms Max	5 Mohms Max	5 Mohms Max	5 Mohms Max	5 Mohms Max
<b>Flash over Voltage</b>	1.2 K.V. Min	1.2 K.V. Min	1 K.V. Min	1.2 K.V. Min	1.2 K.V. Min	2 K.V. Min	2 K.V. Min
<b>Insulation Resistance</b>	1000 Mohms Max	1000 Mohms Max	1000 Mohms Max	1000 Mohms Max	1000 Mohms Max	1000 Mohms Max	1000 Mohms Max
<b>Max. Working Temp</b>	70°C	70°C	70°C	70°C	70°C	100°C	100°C

## Ordering Information

### SPADE TERMINALS

<b>ST-1</b>	<b>Spade Terminal Straight Cut</b>
<b>ST-2</b>	<b>Spade Terminal Side Cut</b>
<b>ST-1 90 Degree</b>	<b>Spade Terminal Straight Cut With 90 Degree Bend</b>

### BINDING POST TERMINALS

<b>GT-3</b>	<b>Terminal – 3 Amp</b>
<b>GTO-5</b>	<b>Terminal – 5 Amp</b>
<b>GTOL-5</b>	<b>Terminal – 5 Amp – Extra Long Threaded Stem</b>
<b>GT-10</b>	<b>Terminal – 10 Amp</b>
<b>GT-15</b>	<b>Terminal – 15 Amp</b>
<b>GT-30</b>	<b>Terminal – 30 Amp</b>

