



SERIES
1050
LOW



TECHNICAL DATA

Material:	Lexan 940
Colour:	Grey (RAL 7035)
Max. temperature:	100° C
Width:	105 mm (6 modules)
Label measurement:	79.6 x 98.0 mm
Self-extinguishing:	Acc. to UL94-V0
IP protection:	IP 20

Material:	Noryl VO 1550
Colour:	Black (RAL 9005)
Max. temperature:	100° C
Max. wire dia.:	2 x 2.5 mm ²
Max. load:	10A (for higher load please inquire)
Terminals:	36 fixed or plugable
Mounting:	DIN-rail (EN50022)
Self-extinguishing:	Acc. to UL94-V0

[illegible]

- | TYPE 1050 LOW: | ORDER CODE: |
|--|----------------|
| Complete, 257 for plugable | p/n 8069001051 |
| Complete, closed, no terminals | p/n 8016910601 |
| Top part, 257, plugable | p/n 8069006101 |
| Top part, grey, closed, no terminals | p/n 8069006101 |
| Base part with clip and 2 screws | p/n 4969021057 |
| DIN-rail clip for 1050 | p/n 0669000604 |
| Packing for 1050 | p/n 2068105000 |
| PCB for 1050 | p/n 4999001050 |
| Terminal for 1050, 257/18, HO/A, PCB part | p/n 1155718580 |
| Terminal for 1050, 256/18, wire part | p/n 1155618080 |
| Terminal for 1050, 605/18, fixed terminals | p/n 3950141808 |
| Screw/selfcutting 2 pcs. | p/n 7006102965 |

Many more p/n available - please enquire.