

JIT Components, Inc.

10930 Endeavour Way, Unit A Seminole FL 33777

Phone: (727) 544-9050

Fax: (727) 544-9273

Email: service@jit-components.com

Cable Glands for Sealed



Required to maintain NEMA 4X rating when cables enter or exit a NEMA 4 or 4X rated enclosure

Assembly consisting of molded black nylon body, hex nut, cable nut and with a rubber gasket and cable seal

Nylon material has UL94 V2 flammability rating and suggested service temperature of -40°C to $+100^{\circ}\text{C}$

PART DATA

Part No	Mount Thread	Cable Range (Dia)	A	B	C	D	E	F	G	H
NG-9511	PG-7	0.118 – 0.169	0.197	0.315	0.488	0.315	1.102	0.039	0.827	0.209
NG-9512	PG-9	0.158 – 0.252	0.283	0.374	0.563	0.323	1.169	0.056	0.921	0.201
NG-9513	PG-11	0.197 – 0.295	0.374	0.512	0.717	0.323	1.236	0.058	1.047	0.205
NG-9514	PG-13.5	0.236 – 0.433	0.453	0.591	0.787	0.371	1.315	0.062	1.161	0.244
NG-9515	PG-16	0.394 – 0.512	0.524	0.669	0.878	0.382	1.425	0.062	1.303	0.250
NG-9516	PG-21	0.512 – 0.669	0.681	0.866	1.102	0.425	1.583	0.062	1.551	0.287
NG-9517	PG-29	0.709 – 0.945	0.957	1.181	1.449	0.433	1.772	0.062	1.972	0.315

